


MM33R

MINIATURE – .20/5mm LEAD SPACING

Radial Box

Capacitance ranges listed are for standard products.
Custom applications are available for all series.



Dimensions (inches/mm)

μF	63VDC			100VDC			250VDC			400VDC			630VDC		
	T	H	L	T	H	L	T	H	L	T	H	L	T	H	L
.001	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5
.0015	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5
.0022	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5
.0033	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5
.0047	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5
.0068	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.20/5.0	.31/8.0	.30/7.5
.01	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.20/5.0	.31/8.0	.30/7.5
.015	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.20/5.0	.31/8.0	.30/7.5
.022	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5
.033	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5
.047	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.47/12	.30/7.5
.068	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.20/5.0	.31/8.0	.30/7.5	.24/6.0	.47/12	.30/7.5
.1	.10/2.5	.26/6.5	.30/7.5	.10/2.5	.26/6.5	.30/7.5	.24/6.0	.39/10.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5	.24/6.0	.47/12	.30/7.5
.15	.10/2.5	.26/6.5	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5			
.22	.14/3.5	.31/8.0	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5			
.33	.14/3.5	.31/8.0	.30/7.5	.14/3.5	.31/8.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5						
.47	.14/3.5	.31/8.0	.30/7.5	.20/5.0	.31/8.0	.30/7.5	.24/6.0	.47/12.0	.30/7.5						
.68	.20/5.0	.31/8.0	.30/7.5	.20/5.0	.31/8.0	.30/7.5									
1.0	.24/6.0	.39/10.0	.30/7.5	.24/6.0	.39/10.0	.30/7.5									
1.5	.24/6.0	.47/12.0	.30/7.5	.24/6.0	.47/12.0	.30/7.5									
2.2	.24/6.0	.47/12.0	.30/7.5	.24/6.0	.47/12.0	.30/7.5									

ALTERNATE CASE SIZES AVAILABLE FOR MOST CAPACITANCE VALUES AND VOLTAGES

HOW TO ORDER

Example:	MM33R	.1μF	10%	100VDC
	Series	*Capacitance	Tolerance	Voltage
Order:	MM33R	1003	K	100

*For capacitance values, list three significant digits with fourth digit indicating number of zeros to follow.

Tolerance: J=5%, K=10%



A division of Pelco Component Technologies

2747 Route 20 East, Cazenovia, NY 13035

phone 315-655-2530 ■ fax 315-655-3862 ■ www.stkelectronics.com